Product Image	Product Features
MODEL: HTP-2 4G Version 	★600W/3K Ultra HD wireless connection ★Remote active wake-up, two-way voice intercom ★500ms quick start, ★Intelligent human movement detection, intelligent alarm push ★Dual lenses, free choice of far and near focus, high definition close at hand ★Low power consumption system optimization, free combination of 4G/WIFI ★Free 3-day cloud storage of alarm video ★Supports external 5W-15W voltage-stabilized solar panels to continuously deliver power and keep the equipment uninterrupted. ★Dual light sources, full color day and night, diversified housing sizes 1.5-2-2.5 optional private model

serial number	category	type	parameter
1	**system**	operating system	Linux
		Number of online users	4 users watch online at the same time
		APP	O-KAM-overseas,Little Eagle Take a Look-Domestic
2	**collection**	processor	T31
		Memory	512Mbit
		Image Sensor	OS02G10+OS02G10, 200W, 1/2.9 CMOS (pixel optional, PCB compatible)
		lens	4mm+12mmTelephoto lens + short focus lens combination IRCUT all-in-one
		Image Sensor	1/2.9 CMOS sensor
		Minimum illumination	0.01Lux
		Sensor performance	Support automatic white balance, automatic gain control, automatic backlight compensation
		night vision	6 infrared + 6 white light dual light sources 20MIL, 850nm wavelength
		Viewing angle	100°/30°
3	**video**	clarity	2304×1296P/15fps/3 million dual streams
		Zoom factor	Binocular stepless 6x hybrid zoom
		night vision	Full color night vision/black and white night vision/intelligent night vision
		Compression standard	H.265 /H.264 /MJPEF/JPEG
		IR control	When the IR is turned on, the night vision function is enabled, and infrared and ICR are automatically detected; when the IR is turned off, the night vision function is disabled, and the infrared is always off, and the ICR is fixed in the day vision mode.
		Code rate	CBR/VBR two code rate control modes, and the output code rate range is 128~4096kbps
		Image adjustment	Brightness, contrast, vertical, horizontal adjustable, OSD display
4	**Audio**	enter	Built-in-38dB microphone
		output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/code rate	G711A
5	**AI**	Humanoid detection	Humanoid detection, filtering invalid alarm events
		object tracking	/
		Area detection	Freely smear and select, only monitor areas that users care about
		Smart notification sound	The push sounds from different devices are differentiated, and you can accurately know which device was triggered.
		Smart alarm sound	Set different device alarm sounds according to different scenarios
		More AI functions (under internal testing)	Pets, vehicles, packages, etc.
6	**Network**	network	Support 4G/WIFI optional
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTMP,P2P,IPV4,IPV6
		wireless network	IEEE802.11b/g/n
		wireless frequency	2.4~2.4835GHz
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
		Wireless connections	AP hotspot distribution network, QR code distribution network
7	**Button/Interface**	USB	Micro usb/charging port
		Button 1	Toggle switch/Toggle left and right to switch on/off mode
		reset button	reset button/long press to restore factory settings
8	**storage**	External TF card	Support T-Flash card (up to 128GB)
		cloud storage	3 days of free recurring cloud storage
9	**Call the police**	Alarm detection	Motion detection/PIR human detection/humanoid detection, the distance can be adjusted in steps, the detection distance can be up to 15M
10	**Physical indicators**	Charging voltage	DC5V±5%
		powered by	Comes with 20000mAh battery power supply, 4*21700
		working environment	Working temperature: -10～55℃, working humidity <90%
		weight	Gross weight: TBD (note: the actual object shall prevail)
		size	
		packing list	Host*1, screw package, MICRO USB*1, instruction manual*1, (solar panel*1, solar panel bracket*1 optional)