SZ-200-MC

Warranty

♦ 2 years Manufacturer Warranty

Manufacturing:

♦ original cell sorting system ensures the best elecrtric cell match
♦ EL-Testing before packing
♦ Comprehensive module power testing

Performace:

♦ Upgraded efficiency and unprecedented flexibility.
♦ Lower operating temperature and excellent thermal performance
♦ Reliable technology with long-term stability and lifespan
♦ Ideal for balconies, RVs, and BIPV applications.



Mechanical Data Standard Test Conditions AM=1.5,E=1000W/m^2,TC=25°C	
Nominal Power	200W
Cell Type	Mono-crystalline
Cell Efficiency	＞22.5%
Maximum Power Current (Impp)	6.64A
Maximum Power Voltage (Vmpp)	30.16V
Open-circuit Voltage (Voc)	35.36V
Short-circuit Current (Isc)	7.03A
Maximum System Voltage	200V
Output Tolerance	0~+3%
Cable (MC4)	900mm/2.5mm^2
Module Structure	CPC/ Cell / EVA/Backsheet
Junction box rating	≥IP67
Diode	√
Operating temperature range	-20°C~+65°C
Packaging	
Module Dimensions	1290*790*2mm
Module Weight	4.2/6.5kg
Package	Single package
Pieces per Pallet	30 pcs
Gross Weight per Pallet	220kg
Pallet Dimensions	1200*1100*940mm

