# SUNNY TRIPOWER 8.0 / 10.0 with SMA SMART CONNECTED





#### Compact

- One-person installation due to low weight of 20.5 kg
- Compact design means minimum space requirements

#### Easy to use

- 100% plug and play installation
- Free online monitoring via SMA Energy App
- Automated service thanks to SMA Smart Connected
- Warranty extension from 5 to 10 years - free of charge

#### High yields

- Use of surplus energy through dynamic active power limitation
- Yield increase without installation effort due to integrated shade management SMA ShadeFix

#### Combinable

- Intelligent energy management and storage solutions can be added anytime
- Can be expanded with SMA Power Limiter for use of a ripple control receiver

# **SUNNY TRIPOWER 8.0 / 10.0**

Higher yields for private homes – intelligent solar power generation

The new Sunny Tripower 8.0–10.0 ensures maximum energy yields for private homes. This inverter combines the integrated SMA Smart Connected service with intelligent technology for all ambient conditions. Thanks to its extremely light design, the device can be installed quickly and easily. The Sunny Tripower can be commissioned quickly via smartphone or tablet thanks to its integrated web interface. For specific requirements on the roof, SMA ShadeFix maximizes the PV system's yield. Current communication standards make the inverter future-proof, meaning intelligent energy management solutions as well as SMA storage solutions can be flexibly added anytime.

## SMA SMART CONNECTED

### Integrated service for ease and comfort

SMA Smart Connected\* is free monitoring of an inverter via the SMA Sunny Portal. If an inverter fails, SMA proactively informs the PV system owner and the installer. This saves valuable working time and costs.

With SMA Smart Connected, the installer benefits from rapid diagnoses by SMA. They can thus quickly rectify the fault and score points with the customer thanks to the additional, attractive services.





#### **ACTIVATION OF SMA SMART CONNECTED**

During registration of the system in the Sunny Portal, the installer activates SMA Smart Connected and benefits from automatic inverter monitoring by SMA.



#### **AUTOMATIC INVERTER MONITORING**

SMA takes on the job of inverter monitoring with SMA Smart Connected. SMA automatically checks the individual inverters for anomalies around the clock during operation. Every customer thus benefits from SMA's many years of experience.



#### PROACTIVE COMMUNICATION IN THE EVENT OF FAULTS

After a fault has been diagnosed and analyzed, SMA informs the installer and end customer immediately by email. Everyone is thus optimally prepared for the troubleshooting process. This minimizes downtime and saves time and money. Regular power reports also provide valuable information about the overall system.



#### REPLACEMENT SERVICE


If a replacement device is necessary, SMA automatically supplies a new inverter within one to three days of the fault diagnosis. The installer can contact the PV system operator of their own accord and replace the inverter.




#### PERFORMANCE SERVICE


The PV system operator can claim compensation from SMA if the replacement inverter is not delivered within three days.

<sup>\*</sup> Details: see document "Description of Services – SMA SMART CONNECTED"





Technical data	Sunny Tripower 8.0	Sunny Tripower 10.0	
Input (DC)			
Max. PV array power	15000 Wp	15000 Wp	
Max. input voltage	1000 V	1000 V	
MPP voltage range	260 V to 800 V	320 V to 800 V	
Rated input voltage	58	80 V	
Min. input voltage / initial input voltage	125 V	/ 175 V	
Max. input current input A / input B		20 A / 12 A	
Max. DC short-circuit current input A / input B		/ / 18 A	
Number of independent MPP inputs / strings per MPP input		, .:2; B:1	
Output (AC)		, =::	
Rated power (at 230 V, 50 Hz)	8000 W	10000 W	
Rated / Max. apparent power	8000 VA / 8000 VA	10000 VA / 10000 VA	
Rated voltage	3 / N / PE; 220 V / 380 V 3 / N / PE; 230 V / 400 V 3 / N / PE; 240 V / 415 V		
Voltage range	180 V to 280 V		
Grid frequency / range	50 Hz / 45 Hz to 55 Hz 60 Hz / 55 Hz to 65 Hz		
Rated grid frequency / rated grid voltage	50 Hz / 230 V		
Rated / Max. output current	3 x 11.6 A / 3 x 12.1 A	3 x 14.5 A / 3 x 14.5 A	
Power factor at rated power / displacement power factor adjustable	1 / 0.8 overexcited	to 0.8 underexcited	
Feed-in phases / connection phases	3	/3	
Efficiency			
Max. efficiency / European efficiency	98.3 % / 97.7 %	98.3 % / 98.0 %	
Protective devices			
Input-side disconnection point	•		
Ground fault monitoring / grid monitoring	•/•		
DC reverse polarity protection / AC short circuit current capability / galvanically isolated	• / • / –		
All-pole-sensitive residual-current monitoring unit	•		
Protection class (according to IEC 61140) / surge category (according to IEC 60664-1)	1,	/ III	
General data			
Dimensions (W / H / D)	460 mm / 497 mm / 176 mm (18	.1 inches / 19.6 inches / 6.9 inches	
Weight	20.5 kg (45.2 lbs)		
Operating temperature range	-25 °C to +60 °C (-13 °F to +140 °F)		
Noise emission, typical	30 dB(A)		
Self-consumption (at night)	5.0 W		
Topology / cooling method	Transformerless / convection		
Degree of protection (according to IEC 60529)	IP65		
Climatic category (according to IEC 60721-3-4)	4K4H		
Max. permissible value for relative humidity ( non-condensing )	100%		
Features			
DC connection / AC connection	SUNCLIX /	AC connector	
Display via smartphone, tablet, laptop	•		
Interfaces: WLAN / Ethernet / RS485	•/•/•		
Communication protocols	Modbus (SMA, Sunspec), Webconnect, SMA Data		
Shade management: SMA ShadeFix (integrated)	•		
Warranty: 5 / 10 / 15 years	• /	• / •* / 0	
Certificates and permits (more available upon request)	AS4777.2, C10/11, CE, CEI 0-21, DEWA 2016, DIN EN 62109-1/IEC 62109-1/IEC 62109-1/IEC 62109-2/IEC 62109-2, DK1/2 Typ A, EN 50549-1, EN 62116, G98 G99-1, IEC 61727, IE-EN 50438, NEN S097-2-1, PPDS, PPC RD 1699, SI 4777.2, TOR Erzeuger Typ A, UTE C15-712, VDE-AR-N 4105, VDE-0126-1-1, VFR 2014		
Certificates and approvals (planned)		16149	
Country availability of SMA Smart Connected	AU, AT, BE, CH, DE, ES, FR, IT, LU, NL, UK		
Type designation	STP8.0-3AV-40	STP10.0-3AV-40	



#### **BASIC SYSTEM functions**

- Easy commissioning via integrated WLAN and Speedwire interface
- Maximum transparency thanks to visualization in Sunny Portal / SMA Energy App
- Safe investment through SMA Smart Connected
- Modbus as interface for third-party providers

#### **Expanded SYSTEM FUNCTIONS**

- Basic system functions
- Reduction in purchased electricity and increase in self-consumption through use of stored solar energy
- Maximum energy use thanks to forecast-based charging
- Increased self-consumption thanks to intelligent load control
- Easy integration of ripple control receivers via SMA Power Limiter

#### With SMA Energy Meter

- Maximum system usage through dynamic limiting of feed-in to the grid between 0% and 100%
- Visualization of energy consumption